



www.flex-ing.com

## EMERGENCY SHUT-OFF DOUBLE POPPET

2828 Fallon Drive  
Sherman, Texas 75090  
Phone: 1.800.333.3599 / 1.903.892.8983  
Fax: 1.800.765.4801 / 1.903.893.9576

### DOUBLE POPPET EMERGENCY SHUT-OFF VALVE

#### Description —

Features a low profile design, rust resistant epoxy coated cast iron body and top, stainless steel shaft and spring, UL Listed fusible link, 3/8" air test plug, and allows for easy U-Bolt or stabilizer bar mounting.

Includes a machined bottom for easy compression fitting connection to secondary containment piping and includes a 2" male threaded connection on the inlet for secondary containment. All models are UL Listed.

#### Application —

Installed on fuel lines at the island surface level in submersible pump system and is designed to prevent spillage and other potential hazards in the event of a fire or impact to the dispenser.

Upon impact, the top of the valve shears allowing the poppet to close and shut-off the product flow. In case of a fire, the poppet will close as the fusible link melts, resulting once again in a safe shut-off of product flow. The seat of the valve is positioned in the lower valve body, which provides a liquid tight seal even if the top is removed.

#### Specifications —

Model	Size	Height	Width	Weight (lbs.)
ESV24DPFC	1½"	6¼"	4"	5.5



#### Double vs. Single Poppet

Secondary poppet prevents spillage from the dispenser in the event the valve is sheared.

Pressure relief valve to relieve pressure build up due to thermal expansion.

### DOUBLE POPPET REPLACEMENT TOP

#### Description —

The top features a rust resistant epoxy coated cast iron body and includes a seal ring.

#### Application —

Replaces the original top if it becomes damaged or sheared.

#### Specifications —

Model	DESCRIPTION	Weight (lbs.)
ESV24RDP	Double Poppet Replacement Top	1.3

