

Description —

Machined nickel plated fittings, stainless steel ferrules & viton seals ensure that the FLEX-ON FR is compatible with petroleum based products, gasoline, diesel, ethanol, E85, and Bio-Diesel inside and out.



NOM. ID		NOM. OD		WEIGHT	
in.	mm.	in.	mm.	lb./ft.	kg./m
5/8	15.9	1	25.4	0.42	0.63
3/4	19.1	1-1/8	28.6	0.45	0.67
1	25.4	1-3/8	34.9	0.52	0.77

FLEX-ON FR rubber compound is specifically engineered to extend service life, address color fade, aging, premature rubber cracking and abrasion, even in the harshest ozone

Application —

Designed for dispensing pump applications which require a hardwall construction. It is used for reel or retractable cable pump applications.

Specifications —

TUBE:	Chemigum® synthetic rubber
REINFORCEMENT:	Wire braid
COVER:	Ozone-resistant rubber
TEMPERATURE:	-40°F to 140°F (-40°C to 60°C)
COUPLINGS:	Machined nickel plated Grip Mate fittings w/ stainless steel ferrules and optional swivel.
PACKAGING:	Bulk, case quantities, individually wrapped: other packing options available upon request.

Available in colors



NOM. ID		NOM. OD		WEIGHT	
in.	mm.	in.	mm.	lb./ft.	kg./m
5/8	15.9	0.98	24.9	0.28	0.42
3/4	19.1	1.15	29.2	0.37	0.55
1	25.4	1.50	38.1	0.60	0.89

FLHFR	1	0	1	0	0	6
Hardwall Prefix	1=5/8" 2=3/4" 3=1"	Length in feet	Length in feet	Length in feet	Length in inches	Length in inches

- FLHFR101006 = Hardwall 5/8" x 10' 6" male x male assembly.
- FLHFR101006SWOE = End part number with SWOE for swivel one end.
- FLHFR101006SWEE = End part number with SWEE for swivel each end.